## MBR 179 MK2





The Maritime Broadband Radio is a smart antenna designed for use in any application where resilient high-speed communication and high-capacity data transfer are crucial for efficient and safe operation. With beamforming the MBR 179 provides steerable high-gain antenna direction in an omnidirectional sector, ideal for vessels and moving assets. With narrow fan shaped antenna diagram, a strong link margin is maintained and continuously updated as the unit is unaffected of vessel movements.

## TECHNICAL SPECIFICATIONS

Range

Operational range<sup>1</sup>

User data

0.7 to 16.5 Mbps

45 km

20 MHz Up to 4 W

21 dBi

**GMSK** 

1x RJ-45

60

Max 57 dBm

Antenna coverage

Omni-directional

360 degrees azimuth

4900 MHz to 5900 MHz

RF specifications

Frequency band<sup>2</sup>

Channel bandwidth

Tx power

Antenna gain EIRP

Modulation

Internal antenna elements

**INTERFACES** 

Fthernet/LAN

**WEIGHTS AND DIMENSIONS** 

MBR unit

8.8 kg, 323 x 323 x 111 mm

**POWER** 

Supply voltage

24 - 48 V DC 210 W Max. power consumption, full TX

**ENVIRONMENTAL SPECIFICATIONS** 

Operational temperature range

MBR Unit

Humidity (operating/storage)

MBR Unit (recommended)

Ingress protection

Radio

Product safety

Environmental

MBR Unit IP66

STANDARDS AND REGULATIONS

MBR is in conformity with RED directive 2014/53/EU EMC ETSI EN 301 843-1

ETSI EN 301 843-7

IEC 60945/EN 60945

ETSI EN 303 276 IEC 61010-1/EN 61010-1

-40°C - +55°C

20 to 100 % RH / 20 to 70 % RH

IEC 60945/EN 60945

DNVGL-CG-0339 (48 V DC)

IACS E10 (48 V DC)

<sup>1</sup>Operational range is dependent on antenna placement and height

Specifications subject to change without any further notice.

## **KONGSBERG SEATEX**

Switchboard: +47 73 54 55 00 Global support 24/7: +47 33 03 24 07 E-mail sales: km.seatex.sales@km.kongsberg.com E-mail support: km.support.seatex@kongsberg.com



<sup>&</sup>lt;sup>2</sup>Configurable range for the single 20 MHz channel