

BRIDGE WING DISPLAY



KONGSBERG



INFORMATION AT YOUR FINGERTIPS

The Bridge Wing Display can be mounted on the bridge wing to monitor vessel speed and heading. It is a touch display, which is quick to install and easy to operate. With one display on each wing, each display will use data from one or two DARPS units. Communication between the DARPS unit and the Bridge Wing Display is done through ethernet.

TECHNICAL SPECIFICATIONS

WEIGHT AND DIMENSIONS

Display unit 1.6 kg, 253 x 198 x 37 mm

POWER

Voltage 18 to 32 V DC
Power consumption 11 W @ 24 V (50% brightness)
14 W @ 24 V (100% brightness)

ENVIRONMENTAL SPECIFICATIONS

Operating temperature range -10 °C to +55 °C
Recommended operating temp. +25 °C
Storage temperature range -25 °C to +70 °C
Operating humidity 95% non-condensing
Enclosure material Die cast and painted aluminium
Enclosure protection IP56 (flush/console)
IP22 (VESA mount)

Specifications subject to change without any further notice.

July 2019

KONGSBERG SEATEX

Switchboard: +47 73 54 55 00
Global support 24/7: +47 33 03 24 07
E-mail sales: km.seatex.sales@km.kongsberg.com
E-mail support: km.support.seatex@kongsberg.com

km.kongsberg.com/seatex



KONGSBERG