MBR 144 OEM





The Maritime Broadband Radio is a smart antenna designed for use in any application where digital high-speed reliable communication and data transfer is crucial for efficient and safe operation. MBR 144 0EM is the low weight, compact version in the MBR family. Designed for customer specific integration, with a flexible form for easy fit into existing platforms. The antenna connections are connector-based, thus the antennas can be adjusted for the customer specific design.

TECHNICAL SPECIFICATIONS

PERFORMANCE

User data 0.7 to 16.5 Mbps

Antenna coverage

Omni-directional 360 degrees azimuth

RF specifications

Frequency band 5725 MHz to 5850 MHz
Channel bandwidth 20 MHz
Typower Up to 1 W

Tx power Up to 1 W Modulation GMSK Antenna connectors 4, SMA

INTERFACES

Ethernet / LAN

2 (optional)

WEIGHTS AND DIMENSIONS

MBR unit (excl. cables and antennas) 260 g, 120 x 78 x 35 mm

POWER

 $\begin{array}{lll} \mbox{Supply voltage} & \mbox{12 - 24 V DC} \\ \mbox{Max. power consumption} & \mbox{25 W} \\ \mbox{Idle} & \mbox{6 W} \end{array}$

ENVIRONMENTAL SPECIFICATIONS

 $\begin{array}{ll} \mbox{Operating temperature range} & -30\ ^{\circ}\mbox{C to } +55\ ^{\circ}\mbox{C} \\ \mbox{Operating humidity} & 20\ to\ 100\ ^{\circ}\mbox{RH} \\ \mbox{Storage humidity (recommended)} & 20\ to\ 70\ ^{\circ}\mbox{RH} \\ \mbox{Ingress protection} & \mbox{IP41} \\ \end{array}$

STANDARDS AND REGULATIONS

MBR is in conformity with RED directive 2014/53/EU

FCC ID Q8IM144M20EM EMC ETSI EN 301 843-1 ETSI EN 301 843-7

IEC 60945/EN 60945 FCC §15.407

 Radio
 FCC §15.407

 Product Safety
 IEC 61010-1/EN 61010-1

 Environmental
 IEC 60945/EN 60945



Specifications subject to change without any further notice.



Switchboard: +47 73 54 55 00 Global support 24/7: +47 33 03 24 07 E-mail sales: km.seatex.sales@km.kongsberg.com E-mail support: km.support.seatex@km.kongsberg.com

