MBR 144





The Maritime Broadband Radio is a smart antenna designed for use in maritime applications where digital high-speed reliable communication and data transfer is crucial for efficient and safe operations. Completely enclosed with integrated antennas the MBR 144 is designed for installations on small manned and unmanned vessels. The unit has an integrated bracket for easy installation on vertical or horizontal rails, and with built-in GNSS sensor, the unit has possibility for absolute positioning. With its neat and slim design, and only one cable to connect, the MBR 144 is easy to deploy on the vessel.

TECHNICAL SPECIFICATIONS

PERFORMANCE

RangeOperational range ¹⁾
User data
20 km
0.7 to 16.5 Mbps

Antenna coverage

Omni-directional 360 degrees azimuth

RF specifications

Frequency band ²⁾
Channel bandwidth
Tx power

4900 MHz to 5900 MHz
20 MHz
Up to 2 W

INTERFACES

Ethernet / LAN 1x RJ 45

WEIGHTS AND DIMENSIONS

MBR Unit 2.5 kg, 260 x 115 x 115 mm

POWER

 $\begin{array}{lll} \text{Supply voltage} & 24\,\text{V DC} \\ \text{Max. power consumption} & 25\,\text{W} \\ \text{Idle} & 7\,\text{W} \end{array}$

ENVIRONMENTAL SPECIFICATIONS

 $\begin{array}{lll} \mbox{Operating temperature range} & -40\ ^{\circ}\mbox{C to } +55\ ^{\circ}\mbox{C} \\ \mbox{Operating humidity} & 20\ \mbox{to } 100\ ^{\circ}\mbox{RH} \\ \mbox{Storage humidity (recommended)} & 20\ \mbox{to } 70\ ^{\circ}\mbox{RH} \\ \mbox{Ingress protection} & \mbox{IP } 66 \end{array}$

STANDARDS AND REGULATIONS

MBR is in conformity with RED directive 2014/53/EU

EMC ETSI EN 301 843-1 ETSI EN 301 843-7 IEC 60945/EN 60945

Radio ETSI EN 303 276

Product Safety IEC 61010-1/EN 61010-1
Environmental IEC 60945/EN 60945

DNVGL-CG-0339

IACS E10

Specifications subject to change without any further notice.







¹⁾ Operational range is dependent on antenna placement and height

²⁾ Configurable range for the single 20 MHz channel