

MEOS™ SENTINEL COLLGS



KONGSBERG



Collaborative Ground Segment (CollGS) for reception and processing of Sentinel-1 data

MEOS™ S-1 CollGS is a processing suite that provides Sentinel-1 products in near real-time.

MAIN BENEFITS

- When a MEOS™ HRDFEP is used for downlink, the MEOS™ S-1 CollGS Dispatcher works in close connection with it by commanding it to filter the NRT ISP distribution by sensing time. This improves near real-time throughput and reduces stress on the TCP network. The whole segment can also be distributed post-pass and processed by MEOS™ S-1 CollGS
- Linux environment that automatically scales to use available processing capacity
- Fully automated production and distribution based on XML schedule files
- Highly configurable Level-0 processor operating on raw data (ISPs) on a direct downlink for near real-time services, post-pass distributed ISP-files (one per channel) or S-1 Level-0 from archive. Produces standard L0 and L0 slices
- Supports Level1 slice processing and post processing assembly of L1 slices for faster processing in a multi ESA IPF configuration
- Supports several processing nodes (ESA IPFs) to increase performance
- Support single and dual polarization

MEOS™ S-1 CollGS ARCHITECTURE


The MEOS™ S-1 CollGS contains several subsystems, as shown in yellow in the figure. The CollGS Dispatcher subsystem distributes processing jobs based on a priority schedule and available processing resources.

The MEOS™ S-1 Level0 processor is specifically designed to operate efficiently in connection with the MEOS™ HRDFEP.

Additional processor nodes (ESA IPF) may be added to the MEOS™ S-1 CollGS to increase throughput. An example of a complete system configuration is also shown in the figure, including MEOS™ Antenna and MEOS™ Dashboard.

FEATURES

- Fast and full featured S-1 CollGS functionality.
- Saves operation costs by automation.
- Supports priority L1-processing for near real-time demands.
- Field expandable capacity and functionality.
- Supports the official ESA IPF, including L1 slicing and assembly.
- Provides S-1 L0 standard and slice products.
- Optimized for near real-time services.
- Supports filtered NRT-distribution from MEOS™ HRDFEP.



TECHNICAL SPECIFICATIONS

MEOS™ SENTINEL-1 COLLGS PERFORMANCE DATA

MEOS™ Sentinel-1 CollGS Performance

With MEOS™ S-1 CollGS the user may prioritize downlink segments or parts of segments that are needed for near real-time services. This feature requires the MEOS™ HRDFEP as front end. This is done through a filter XML file which lists prioritized sensing time segments for near real-time products.


The CollGS Dispatcher unit distributes this filter XML file to the MEOS™ HRDFEP, which sends the prioritized segments via TCP/IP as soon as they are available. ISP files of the complete dump may also be distributed post-pass.

Observed processing performance with four ESA IPFs (24 cores), one MEOS™ HRDFEP and L1 slicing processing enabled:

Product type	Processing performance	Comments
IW-GRDM	15 min 31 s	6 L1 slices, approx. 2 min 40 s raw ISP data
IW-GRDM	8 min 30 s	2 L1 slices, approx. 1 min raw ISP data
IW-GRDH	7 min 57 s	1 L1 slice, approx. 30 s raw ISP data
EW-GRDM	7 min 14 s	2 L1 slices, approx. 2 min raw ISP data
EW-GRDM	7 min 42 s	3 L1 slices, approx. 2 min 30 s raw ISP data
EW-GRDH	8 min 30 s	2 L1 slices, approx. 2 min raw ISP data

We have delivered an operational configuration with three MEOS™ HRDFEPs, one server with MEOS™ S1 Level0 Processor and six ESA IPF servers.

The system is fully integrated and capable of receiving and processing from two MEOS™ HRDFEPs simultaneously. The system configuration is flexible with respect to setup for lower or higher performance according to your demands.



Specifications subject to change without any further notice.

MEOS™ is a registered trademark of Kongsberg Defence & Aerospace AS - Spacetec in Norway and other countries

KONGSBERG DEFENCE & AEROSPACE AS
SPACETEC

Telephone: +47 77 66 08 00
E-mail sales: marketing@spacetec.no
spacetec.no



KONGSBERG