





K-TACS - KONGSBERG TACTICAL COMMUNICATIONS SYSTEM

THOR - Tactical SDR

THOR, a dual channel tactical Software Defined Radio (SDR), provides resilient wide band and narrow band connectivity to warfighting platforms and units. The waveforms provide unique EPM performance to ensure communications in harsh environments. THOR is built to meet the requirements to tactical communications of the next decades.

THOR is optimized for tactical mobile platforms. The warfighter may apply the two independent VHF/UHF-radio channels for simultaneous voice and data communications on narrowband and wideband selectable waveforms.

Electromagnetic Spectrum Operations

THOR facilitate increased awareness and coordinated spectrum operations. The EPM performance is provided by the advanced waveforms. THOR can be used as a sensor for advanced EMSO. This novel design combine wireless tactical voice and data traffic capabilities with advanced algorithms taking full advantage of the THOR sensor capabilities. Increasing spectrum awareness allows for better utilization and survivability of own communication in the contested spectrum.

Waveforms

THOR can accompany a wide range of NATO standard and KONGSBERG proprietary waveforms making each radio a valuable tool for its user. Combining waveforms to counter the EW threats when needed and transport data at high rates when possible.

KONGSBERG EPM narrow band waveform utilize a patented Narrow Band Direct Sequence Spread Spectrum technology in combination with Frequency Hopping. This provides exceptional range, coverage and the ability to operate in severe multipath conditions, making THOR a highly effective tool for on-the-move combat connectivity.

Design features

THOR provides embedded AES256 encryption ensuring high-level security in the network. The flexibility of the SDR architecture supports customer tailored crypto systems.

THOR is designed to support an Evolutionary Capability Development (ECD). THOR provides a capable, resilient, and highly adaptable platform, with open interfaces to support customer requested or 3rd party software modules.

FEATURES

- Dual channel two independent full performance channels
- Direct sequence spread spectrum and frequency hopping technologies for maximum EPM performance
- Built in full co-site capabilities
- SCA 4.1 architecture
- Advanced networking features
- Compact form factor



kongsberg.com 1234567890/AA

Land Systems

Land Systems deliver world class robust and network centric communications solutions and precision engagements with maximum effect and protection. All products in the K-TaCS family are high quality ruggedized-by-design equipment for use in advanced military tactical communication systems.



Advanced network functionality



Superior coverage



Excellent performance in time critical fire support applications



THOR Radio Control Terminal

TECHNICAL DATA

RF CHARACTERISTICS Frequency range: 30 – 1525 MHz

RF Bandwidth: 5 kHz to 10 MHz

Output Power: 2x20 W

WAVEFORMS KONGSBERG proprietary EPM and non-EPM WF,

including WBWF optimized for AD applications

NATO STANAG 5630 NBWF NATO STANAG 4732 SATURN

NATO STANAG 4204 Single channel FM

NATO STANAG 5651 NHDR or

STANAG 5649 NHCDR

NATO STANAG 4681 IW SATCOM (optional)

DMR (optional)

DATA CAPACITIES Waveform dependent

From 600 bps to 2.5 Mbit/s or more

INTERFACES 2x2 TNC RF, Configurable antenna selection

4x LAN Ethernet 10/100/1000BASE-T/TX w/PoE

USB

Key loading EKMS/DS-101 compatible GNSS w/pps (internal and external) System expansion Interfaces

System expansion interraces

Network Service: IPv4/IPv6 External Networks: OSPF, RIP Embedded encryption: AES256

Voice encoding: MELPe 600/1200/2400 bit/s

STaC-IS/TSVCIS compatible NINE/Tactical NINE supported

MANAGEMENT Web

SERVICES

TLS/OpenConfig/Yang/JSON

POWER SUPPLY 11 – 33 VDC

MIL-STD 1275

150 W single, 200 W dual power consumption

Phone: +47 32 28 82 00 E-mail: dls.post@kongsberg.com WEB: https://www.kongsberg.com/kda/products

ENVIRONMENTAL Operating temp.: -40°C to +55°C

Environmental: MIL-STD 810 army ground

EMC: MIL-STD 461 army ground

DIMENSIONS H/W/D: 125 mm / 210 mm / 360 mm

Weight: 8,9 kg

