





Maritime Broadband Radio

The Maritime Broadband Radio (MBR) is a smart antenna designed for use in any application where resilient high-speed communication and high-capacity data transfer are crucial for efficient and safe operation. With beamforming the MBR 179 MK2 provides steerable high-gain antenna direction in an omnidirectional sector, ideal for vessels and moving assets. With a narrow fan shaped antenna diagram, a strong link margin is maintained and continuously updated as the unit is unaffected of vessel movements.

Technical specifications

Performance

User data throughput 0.7 - 16.5 Mbps

Antenna coverge

Omni-directional 360 degrees azimuth

RF specifications

Frequency band¹ 4900 - 5900 MHz
Channel bandwidth 20 MHz
Antenna gain 21 dBi
EIRP Up to 57 dBm
Modulation GMSK

Internal antenna elements 60

Interfaces

Ethernet/Power connector 1 x MIL-STD-38999 13-26

Marine Bronze

Data interface Ethernet 10/100 baseT

Weight and dimensions

Dimensions $323 \times 323 \times 111 \text{ mm}$

Weight 9 kg

Power specifications

Supply voltage 24 - 48 VDC Power consumption, full Tx Power consumption, Rx only 70 W

Environmental specifications

Operating temperature -40 °C - +55 °C

Ingress protection IP66

Standards and regulations

MBR is in conformity with RED directive 2014/53/EU

EMC ETSI EN 301 843-1

ETSI EN 301843-7 IEC 60945/EN 60945

Radio ETSI EN 303 276

Product safety IEC 61010-1/EN 61010-1

Environmental IEC 60945/EN 60945 DNVGL-CG-0339 (48 VDC)

IACS E10 (48 VDC)

Specifications subject to change without any further notice.

¹ Configurable range for the single 20 MHz channel