

KCC 200 D



KONGSBERG



Uncompromising maritime imagery

The navigator's eyes are always on watch. A camera platform with exceptional precision and reliability is essential to replace or assist the navigator's eyes. The KONGSBERG Camera Cluster 200 D (KCC 200 D) delivers just that, housed in a compact and durable casing.

The D version utilizes 3 highly sensitive machine vision cameras to create a 250° panorama. Our unique contrast-enhancing algorithms deliver images with a high-dynamic range and an outstanding low-light performance.

Each camera is meticulously calibrated to correct lens distortions, enabling high-quality stitching and accurate pixel data.

Technical specifications

Performance

Image frame rate	Up to 4 FPS
Image protocol	JPEG over RTP or TCP
Video frame rate	24 FPS
Video protocol	RTP/RTSP
Video compression	H.264/H.265
Resolution	3x 3856x2180 px (8.3 Mpx)
Field of view	249.4° (h) x 55.4° (v)

Input/Output

Gigabit Ethernet

Weights and dimensions

Sensor Unit	
Dimensions	301 × 351 × 176 mm
Weight	8.3 kg
Mounting bracket, standard	0.5 kg

Junction Box

Dimensions	240 × 110 × 100 mm
Weight	3.2 kg

Power specifications

Sensor Unit	
Supply voltage	12 - 30 VDC
Power consumption, mean	20 W
Power consumption, max	75 W

Junction Box

Supply voltage	230 VAC
Power consumption, max	75 W

Environmental specifications

Sensor Unit	
Operating temperature	-20 - +55 °C
Storage temperature	-30 - +80 °C
Enclosure protection	IP66

Junction Box

Operating temperature	-20 - +55 °C
Storage temperature	-20 - +70 °C
Enclosure protection	IP66

Standards and regulations

Electromagnetic compatibility, EMCD, immunity/emission	IEC 60945, IACS E10
--	---------------------

Product safety

Compliance to LVD	IEC 62368-1:2020
-------------------	------------------

Specifications subject to change without any further notice.