


**LITHIUM CELLS OR BATTERIES TEST SUMMARY
IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TEST AND CRITERIA**

BATTERY TRANSPORTATION INFORMATION

Name of battery : Item Number : 369215 Item Name : Battery Pack for PX Multisensor Item Description : Assembled battery (LiFePO4)		Battery manufacturer's contact information : Kongsberg Maritime Strandpromenaden 50 3190 Horten Norway +47 33034000 www.simrad.com																																									
Name of the test laboratory : Ansmann AG Industriestraße 10 97959 Assamstadt Germany +49 (0) 6294 / 4204 - 4808 www.ansmann.de		Test report id. number: TZ_000008_UN	Date of the test report: 23.08.2012																																								
Description of battery: This Battery is used in the following PX Trawl Sensors: PX Multisensor Mk1 PX Multisensor Mk3 PX TrawlEye Battery type : Lithium Ion (LiFePO4) Battery energy : 58 Wh Battery dimensions : l: 180 / h: 60 / w: 80 [mm] Battery weight : 0.88 kg		List of tests conducted and results (i.e. pass/fail) : <table border="0"> <tr> <td>Test T.1</td> <td>:</td> <td>Altitude Simulation</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.2</td> <td>:</td> <td>Thermal test</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.3</td> <td>:</td> <td>Vibration</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.4</td> <td>:</td> <td>Shock</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.5</td> <td>:</td> <td>External short circuit</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.6</td> <td>:</td> <td>Impact/Crush</td> <td>:</td> <td>Not applicable</td> </tr> <tr> <td>Test T.7</td> <td>:</td> <td>Overcharge</td> <td>:</td> <td>Pass</td> </tr> <tr> <td>Test T.8</td> <td>:</td> <td>Forced discharge</td> <td>:</td> <td>Not applicable</td> </tr> </table> Additional testing comments :		Test T.1	:	Altitude Simulation	:	Pass	Test T.2	:	Thermal test	:	Pass	Test T.3	:	Vibration	:	Pass	Test T.4	:	Shock	:	Pass	Test T.5	:	External short circuit	:	Pass	Test T.6	:	Impact/Crush	:	Not applicable	Test T.7	:	Overcharge	:	Pass	Test T.8	:	Forced discharge	:	Not applicable
Test T.1	:	Altitude Simulation	:	Pass																																							
Test T.2	:	Thermal test	:	Pass																																							
Test T.3	:	Vibration	:	Pass																																							
Test T.4	:	Shock	:	Pass																																							
Test T.5	:	External short circuit	:	Pass																																							
Test T.6	:	Impact/Crush	:	Not applicable																																							
Test T.7	:	Overcharge	:	Pass																																							
Test T.8	:	Forced discharge	:	Not applicable																																							
Reference to assembled battery testing requirements, (i.e. 38.3.3 (f) and 38.3.3 (g)) : Not applicable	Reference to revised edition of the Manual of Tests and Criteria : Revision 5	Does the battery comply with the 30% state of charge (SOC) : Yes																																									
PRODUCT CLASSIFICATION FOR TRANSPORT (According to UN - DGP)																																											
UN Classification : UN 3480		Shipping name : Lithium Ion batteries																																									
Signature (name and title) : Thor Bærhaugen /  Product Manager Catch Monitoring System		This document remains valid as long as no changes, modifications, or additions are made to the battery described in this document, after being transported from Kongsberg Maritime's facilities. This battery has been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of certification. The battery must be packed, labeled and documented according to country and other international regulations for transportation.																																									
Date : 09.12.2019																																											